

Facade Clean

Product properties

Highly effective alkaline cleaning agent for cleaning painted wood and masonry. Effectively cleans all types of dirt.

- Effectively cleans all types of soiling
- Can be sprayed on
- Excellent for wood, brick and metal



Product use

Used for cleaning very dirty painted wood, masonry and sheet metal before painting.

Substrate

Surfaces must be clean, dry, solid and suitable for treatment.

Treatment

Remove loose material and paint by cleaning and sanding.
Effectively removes all types of soiling.

Application

Dose according to instructions.

Apply with a paintbrush, brush or low-pressure spray.

Avoid cleaning warm surfaces which have been exposed to sunshine as this can lead to an uneven gloss on painted surfaces.

Pre-water highly absorbent surfaces.

Allow the solution to work for 5-20 min. without drying out.

The surface can then be scrubbed with a brush to effectively dissolve the dirt.

Afterwards, rinse thoroughly with clean water until all the cleaning agent has been removed.

Expected result

Clean surface ready for paint treatment, if desired.

Please note!

Avoid applying to surfaces that have been heated by the sun.

Environmental information

Remove the cap before sorting the packaging for recycling.

Storage: Cool, frost-free and tightly closed

Technical Data

Product Type	Cleaning
pH	9
Mixing ratio	Periodic cleaning: 1 litre per 15 litres of water. Washing before painting: 1 litre per 5 litres of water.
Dosing	1:5
Nominal spreading rate (m ² /ltr.)	6
Min. working temp. during application and drying/curing	Min. +5°C
Dilution	Water
Cleaning of Tools etc.	Water

Current TDS Version

May 2024

Replaces TDS Version

March 2024